

Datasheet 5798201

5W Argent Modul 329lm 2800-2000K 60° dim



Dimmable:

Our 5W Argent recessed module is designed for the conversion of standard recessed luminaires. The shallow recess depth of only 37mm also allows for use in cavity ceilings with limited space. The high colour rendering index of RA>90 withstands the highest demands on light. Auf Grund des optimalen Wärmemanagement kann eine sehr hohe Lebensdauer erreicht werden. Das Modul besitzt die Dim-To-Warm Technologie und zeichnet sich mit der Absenkung der Lichtfarbe beim Dimmen von 2.800K zu 2.000K aus. The lamp changes the light colour when dimmed in the same way as a traditional incandescent lamp. The many variants of the module in terms of light colour and beam angles enable a wide coverage of the various fields of application. If you would like to know which dimmers this product is compatible with, please follow the link to the test results from our own workshop.

Recommended dimmer: www.sigor.de/dimmerliste


329 lm	luminous flux [lm]
5,00 Watt	rated power
40 Watt	equivalent incandescent lighting
2800-2000 K	colour temperature
Ra>90	colour rendering
<6 sdcn	colour consistency
60°	beam angle

Anschlussleitu	base
Modul	outer bulb
klar	type of glass
37 mm	length
50 mm	diameter
IP30	type of protection
-10° - 40°C	temperature range in operation

0.78	power factor
230 V AC	voltage
50/60 Hz	operating frequency
300 mA	current
6 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.1 s	starting time

Ø 50.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



ENERGY

SIGOR
5798201

A
B
C
D
E
F
G

6
kWh/1000h

2019/2015

as of: 04.09.2023

