

Datasheet 5797801

5W Argent Modul 341lm 2800-2000K 36° dim

Our 5W **Argent recessed module** The module has the Dim-To-Warm technology and features the lowering of the light color when dimming from 2,800K to 2,000K. The lamp changes the light color when dimming as a traditional incandescent lamp.

The many variants of the module in light color and beam angles allow a wide coverage of different fields of application.



Dimmable: yes

Recommended dimmer: www.sigor.de/dimmerliste


341 lm	luminous flux [lm]
5,00 Watt	rated power
40 Watt	equivalent incandescent lighting
2800-2000 K	colour temperature
Ra>90	colour rendering
<6 sdcn	colour consistency
36°	beam angle

Anschlussleitu	base
Modul	outer bulb
klar	type of glass
37 mm	length
50 mm	diameter
IP20	type of protection
-10° - 40°C	temperature range in operation

0,78	power factor
230 V AC	voltage
50/60 Hz	operating frequency
300 mA	current
6 kWh/1000h	energy consumption
<0.5 s	warm-up time up to 60% of the full light output
<0.1 s	starting time

Ø 50.000 h	nominal life time
L70B50	rated life time L70/B50
0.7	lumen maintenance factor at the end of the nominal life

Spectral power distribution
in the range 180 - 800 nm



ENERGY

SIGOR
5797801

A
B
C
D
E
F
G

6
kWh/1000h

2019/2015

as of: 25.11.2022